Printing date 05/26/2023

Reviewed on 05/26/2023

1 Identification

- · Product identifier
- · Trade name:
- · Article number: 2863
- · Application of the substance / the mixture Water treatment
- · Uses advised against
- Processes involving extreme heat use advised against.

Any use carrying a risk of direct contact with eyes/skin where workers are exposed without adequate personal protective equipment (PPE).

Any use involving aerosol formation or vapour release in excess of the assigned WEL where workers are exposed without suitable RPE.

Processes where workers who may be pregnant or breastfeeding could potentially come into direct contact with the undiluted product.

The product is intended exclusively for industrial and professional use.

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:
- · Information department: Product safety department.

· Emergency telephone number:

CHEMTREC: 800-424-9300 (Domestic North America) OR 703-527-3887 (International, collect calls accepted).

2 Hazard(s) identification

· Classification of the substance or mixture

GHS05 Corrosion

Skin Corrosion 1B H314 Causes severe skin burns and eye damage.

Eye Damage 1 H318 Causes serious eye damage.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms GHS05
- · Signal word Danger
- Hazard-determining components of labeling: 2-diethylaminoethanol
- · Hazard statements
- Causes severe skin burns and eye damage.
- Precautionary statements
- Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection.

- If swallowed: Rinse mouth. Do NOT induce vomiting.
- If on skin: Wash with plenty of water.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

· Classification system:

• NFPA ratings (scale 0 - 4)



Health = 3 Fire = 1 Reactivity = 0

Printing date 05/26/2023

Reviewed on 05/26/2023

(Contd. of page 1)

10-25%

10-25%

· HMIS-ratings (scale 0 - 4)

HEALTH	3	Health $= 3$
FIRE	1	Fire $= 1$
REACTIVITY	0	Reactivity $= 0$

· Other hazards

- \cdot Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

 \cdot **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

- 100-37-8 2-diethylaminoethanol
- 532-32-1 Benzoic acid, sodium salt

4 First-aid measures

- \cdot Description of first aid measures
- \cdot General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:
- Immediately rinse with water.
- If skin irritation continues, consult a doctor.
- · After eye contact:
- Check for and remove any contact lenses.
- Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

- If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
- · Information for doctor: Treat symptomatically and supportively.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- \cdot Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- \cdot For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot Special hazards arising from the substance or mixture
- Corrosive.

During heating or in case of fire poisonous gases are produced.

Solid product. Product will melt and combustion may occur when exposed to fire conditions.

- · Advice for firefighters
- Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

Wear fully protective suit.

(Contd. on page 3)

US

Printing date 05/26/2023

Reviewed on 05/26/2023

• Additional information Cool endangered receptacles with water spray.	(Contd. of page 2)	
6 Accidental release measures		
 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Wear protective equipment. Keep unprotected persons away. Keep ignition sources away - no smoking. Environmental precautions: Do not allow to penetrate the ground/soil. Do not allow to enter sewers/ surface or ground water. Methods and material for containment and cleaning up: Pick up mechanically. Send for recovery or disposal in suitable receptacles. Ensure adequate ventilation. Reference to other sections See Section 7 for information on safe handling. See Section 13 for disposal information. Protective Action Criteria for Chemicals 		
• PAC-1:		
7757-83-7 Sodium sulphite	11 mg/m ³	
100-37-8 2-diethylaminoethanol	6 ppm	
532-32-1 Benzoic acid, sodium salt	61 mg/m ³	
• PAC-2:	<u>. </u>	
7757-83-7 Sodium sulphite	120 mg/m ³	
100-37-8 2-diethylaminoethanol	83 ppm	
532-32-1 Benzoic acid, sodium salt	680 mg/m ³	
• PAC-3:		
7757-83-7 Sodium sulphite	710 mg/m ³	
100-37-8 2-diethylaminoethanol	500 ppm	
532-32-1 Benzoic acid, sodium salt	810 mg/m ³	

7 Handling and storage

· Handling:

· Precautions for safe handling

Avoid direct contact (skin/eye contact, ingestion and/or inhalation of fume/mist/dust) with the product in the undiluted form.

Prevent formation of dust.

Ensure good ventilation/exhaustion at the workplace.

Do not mix with acids.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
 Do not store in aluminium, copper, zinc containers.
 Information about storage in one common storage facility:
- Store away from oxidizing agents. Store away from foodstuffs. Do not store together with acids.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · Storage class: 8 A

(Contd. on page 4)

Reviewed on 05/26/2023

(Contd. of page 3)

 \cdot Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Com	· Components with limit values that require monitoring at the workplace:	
100-3	37-8 2-diethylaminoethanol	
PEL	Long-term value: 50 mg/m ³ , 10 ppm Skin	
REL	Long-term value: 50 mg/m ³ , 10 ppm Skin	
TLV	Long-term value: 2 ppm Skin	
532-3	32-1 Benzoic acid, sodium salt	
TLV	Long-term value: 2.5 mg/m ³ inh. fraction, Skin, A5	

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:

Select PPE appropriate for the operations taking place taking into account the product properties.

- · General protective and hygienic measures:
- Do not eat, drink, smoke or sniff while working.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Do not breathe dust

Take note of assigned Workplace Exposure Limits.

· Breathing equipment:

Use suitable respiratory protective device in case of insufficient ventilation.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

If respiratory protection is required, institute a complete respiratory protection program including selection, fit testing, training, maintenance and inspection.

· Protection of hands:



Protective gloves conforming to EN374.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles conforming to EN166.

US

Printing date 05/26/2023

Reviewed on 05/26/2023

(Contd. of page 4)

· Body protection:



Impervious protective clothing

Body protection must be chosen depending on product properties, activity and possible exposure.

9 Physical and chemical properties

> A Aystein and chemical properties		
 Information on basic physical and chemical properties General Information Appearance: 		
Form:	Solid	
Color:	Various colors	
· Odor:	Amine-like	
· Odor threshold:	Not determined.	
· pH-value at 20 °C (68 °F):	9.5 (4%)	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
· Flash point:	>93 °C (>199.4 °F)	
· Flammability (solid, gaseous):	Not determined.	
· Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure:	Not applicable.	
· Density at 20 °C (68 °F):	1.43123 g/cm ³ (11.94361 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not applicable.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
Water:	Soluble.	
· Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
· Other information	NOTE: The physical data presented above are typical values and should not be construed as a specification.	

10 Stability and reactivity

• Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

(Contd. on page 6)

US

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/26/2023

Reviewed on 05/26/2023

· Possibility of hazardous reactions

The product is a strong base, it reacts violently with acid and is corrosive. Reacts violently with strong oxidants causing fire hazard.

- \cdot Conditions to avoid No further relevant information available.
- Incompatible materials: Strong acids and oxidising agents

• Hazardous decomposition products: Nitrogen oxides (NOx)

Carbon monoxide and carbon dioxide Sulfur oxides (SOx)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

Acute tox				
· LD/LC50	· LD/LC50 values that are relevant for classification:			
ATE (Act	ATE (Acute Toxicity Estimate)			
Oral	LD50	5,280 mg/kg (rat)		
Dermal	LD50	3,540 mg/kg		
Inhalative	LC50/4 h	18.4 mg/l (rat)		
100-37-8	100-37-8 2-diethylaminoethanol			
Oral	LD50	1,320 mg/kg (rat)		
Dermal	LD50	885 mg/kg (Guinea pig)		
Inhalative	LC50/4 h	4.6 mg/l /Vapours (rat)		

- · Primary irritant effect:
- \cdot on the skin: Caustic effect on skin and mucous membranes.
- \cdot on the eye:
- Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

ROUTES OF EXPOSURE: The component substances can variously be absorbed into the body by inhalation, through the skin and by ingestion.

EFFECTS OF SHORT-TERM EXPOSURE: The product is corrosive to the eyes, the skin and the respiratory tract. Corrosive on ingestion. May cause effects on the central nervous system.

Contains sulfites. Repeated or prolonged inhalation exposure to sulfites may cause asthma.

The symptoms of asthma often do not become manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation are therefore essential. Anyone who has shown symptoms of asthma due to sulfites or sulfur dioxide should avoid all further contact with this product.

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of oesophagus and stomach.

	Carcinogenic categories
•	IARC (International Agency for Research on Cancer)
]	None of the ingredients is listed.
•]	NTP (National Toxicology Program)
]	None of the ingredients is listed.

(Contd. on page 7)

Reviewed on 05/26/2023

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

100-37-8 2-diethylaminoethanol

EC50 (96 h) 147 mg/l (Fish)

EC50 (48 h) 165 mg/l (Daphnia)

- **Persistence and degradability** The organic portion of the product is biodegradable.
- · Behavior in environmental systems:
- Bioaccumulative potential Product is not expected to bioaccumulate.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- \cdot Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Recommended Hierarchy of Controls:

- Minimize waste;
- Reuse if not contaminated;
- Recycle, if possible; or
- Safe disposal (if all else fails).

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Contact waste processors for recycling information.

Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

- · Uncleaned packagings:
- · Recommendation:

Container remains hazardous when empty. Continue to observe all precautions.

Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

• Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number · DOT, ADR, IMDG, IATA	UN3263	
• UN proper shipping name • DOT	Corrosive solid.	b

Corrosive solid, basic, organic, n.o.s. (2-Diethylaminoethanol)

(Contd. on page 8)

Printing date 05/26/2023

Reviewed on 05/26/2023

	(Contd. of page
· ADR	UN3263 CORROSIVE SOLID, BASIC, ORGANIC, N.O.S (2-DIETHYLAMINOETHANOL)
· IMDG, IATA	CORROSIVE SOLID, BASIC, ORGANIC, N.O.S. (2 DIETHYLAMINOETHANOL)
· Transport hazard class(es)	
· DOT	
· Class · Label	8 Corrosive substances 8
· ADR, IMDG, IATA	٥
· Class · Label	8 Corrosive substances 8
	0
 Packing group DOT, ADR, IMDG, IATA 	П
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Corrosive substances
 Hazard identification number (Kemler code): EMS Number: 	80 F-A,S-B
· Segregation groups	(SGG18) Alkalis
· Stowage Category	B
· Segregation Code	SG35 Stow "separated from" SGG1-acids
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
· ADR	
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 g
	Maximum net quantity per outer packaging: 500 g
· IMDG	
· Limited quantities (LQ)	1 kg
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 g
	Maximum net quantity per inner packaging: 50 g Maximum net quantity per outer packaging: 500 g
· UN "Model Regulation":	UN 3263 CORROSIVE SOLID, BASIC, ORGANIC N.O.S. (2-DIETHYLAMINOETHANOL), 8, II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

(Contd. on page 9)

US

Printing date 05/26/2023

Reviewed on 05/26/2023

	(Contd. of page
-	Toxic Substances Control Act):
	ponents have the value ACTIVE.
	ous Air Pollutants
	the ingredients is listed.
Proposit	
	als known to cause cancer:
	the ingredients is listed.
	als known to cause reproductive toxicity for females:
None of	the ingredients is listed.
Chemica	als known to cause reproductive toxicity for males:
None of	the ingredients is listed.
Chemica	als known to cause developmental toxicity:
None of	the ingredients is listed.
Cancero	ogenity categories
	nvironmental Protection Agency)
None of	the ingredients is listed.
TLV (T	hreshold Limit Value)
None of	the ingredients is listed.
NIOSH-	Ca (National Institute for Occupational Safety and Health)
None of	the ingredients is listed.
The prod Hazard	bel elements luct is classified and labeled according to the Globally Harmonized System (GHS). pictograms GHS05 y ord Danger
2-diethyl Hazard Causes s Precauti Do not b Wear pro If swallo If on skin IF INHA	determining components of labeling: laminoethanol statements evere skin burns and eye damage. ionary statements reathe dusts or mists. otective gloves/protective clothing/eye protection/face protection. wed: Rinse mouth. Do NOT induce vomiting. n: Wash with plenty of water. LED: Remove person to fresh air and keep comfortable for breathing. s: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to certain g.
National	l regulations:
Informa	tion about limitation of use:
	Change in 61
Class	Share in %

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact:
- · Date of preparation / last revision 05/26/2023
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 10)

Printing date 05/26/2023

Reviewed on 05/26/2023

	(Contd. of page 9)
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
Skin Corrosion 1B: Skin corrosion/irritation – Category 1B	
Eye Damage 1: Serious eye damage/eye irritation – Category 1	LIC.